



- Notes:
- 1.Type:Film to Film
 - 2.Operating Voltage:≤10v
 - 3.Operation Temperature:-20℃~65℃
Storage Temperature:-30℃~70℃
 - 4.Life Time:1.000.000 times
 - 5.Connect Material:FPC
 - 6.Response Time:≤10ms
 - 7.Linearity:≤1.5%
 - 8.Transmittance:≥75%
 - 9.Surface Hardness≥3H(pencil)
 - 10.Operation force:60g~150g
 - 11.Resistance:X:333Ω-814Ω Y:220Ω-536Ω

TOLERANCES
(UNLESS OTHERWISE STATED)
DECIMALS ANGLES ±0.5°

>2000MM	±2.00MM
1600< X ≤2000MM	±1.20MM
1200< X ≤1600MM	±0.80MM
800< X ≤1200MM	±0.50MM
400< X ≤800MM	±0.40MM
120< X ≤400MM	±0.30MM
30< X ≤120MM	±0.20MM
<30MM	±0.10MM

格林触控
GreenTouch
GreenTouch Technology Co.,Ltd

Model No.:	GT-4W-17A-2	Size	17"	Ratio	4:3
Structure	F+F	Unit	mm	Scale	1:1
Design	李俊	Date	2015.6.5	Page	1/1
Check	付作书	Date	2015.6.5	Version	A0
Release	汪康	Date	2015.6.5		

由 Autodesk 教育版产品制作

由 Autodesk 教育版产品制作