

1100CMH 110" LCD touch all-in-one PC

Greentouch's 1100CMH 110" series conference machine adopts the perfect combination of the current Android operating system and the dual operating system of X86 hardware. It integrates many technologies such as high-definition display, human-computer interaction, multimedia information processing and network transmission, making it easy to write on the conference machine. Annotation, synchronous interaction, multimedia, remote video conferencing, etc., greatly improve communication efficiency in applications such as conferences, presentations, industry command, deployment, etc., and are the preferred solutions for office, teaching, and graphic interactive presentations in the information age.

Features

- Optional touch technologies include: Greentouch infrared;
- Built-in pluggable PC module
- Ultra-thin body
- Ultra-low standby power consumption
- One key switch
- Automatic switching of external video
- Worldwide agency approvals
- One year standard warranty


- "Designing for Touch" as the base
- Outstanding quality, reliability and Cost-effective

About GreenTouch

Shenzhen GreenTouch Technology Co., Ltd. is a professional manufacturer of product. Our company specializes in R&D, manufacture and marketing of high-grade touch screen and value-added touch machine. Our company has our own brand—Green-Touch and provides customers with touch products including SAW touch screen, IR touch screen, four-wire touch screen, five-wire touch screen, various touch screen monitors and touch all in one PC TV. GreenTouch has automatic production lines and the sealed dust-free workshops and has been certified to ISO9001 Quality Management System. The products are inspected in strict accordance with the quality management system. Quality management becomes an essential part of operation. Our products have been certified to CE, FCC, ROHS. The objective of GreenTouch is to become the most reliable supplier of touch screen, high value-added and special touch products and touch solutions in the world.

Applications

- Education and training field
- Game and Entertainment
- Industrial Automation
- Self-checking service



Specifications

Size	110"	
Model	GT-TC-1100CMH	
Exterior	Shell material	Aluminum alloy frame, black
	Dimensions(mm)	2514.6 x 1503.2 x 123.6MM
LCD	Screen type	105" diagonal, 16:9, Active matrix TFT LCD
	Useful screen area(mm)	2436.5(H) x 1370.52(V)
	Resolution	3084x 2160 @ 120Hz
	Brightness (typical)	350cd/m2
	Contrast ratio	1200:1
	Colors	8 bit/ 16.7 Million
	Viewing angle (from center)	Horizontal (left/right): 89/89° , or 178° in total; Vertical (up/down): 89/89° , or 178° in total
Infrared touch screen parameters	Touch type	Infrared touch screen
	Touch points	20
	Touch drive mode	HID free drive
	Touch screen glass	4MM tempered glass
	Touch screen sensing method	Fingers or other non-transparent touch-sensitive media
	Touch screen positioning resolution	4096X4096
	Touch system communication port	USB 2.0
	Detection function and calibration	With software automatic detection function
	Responding speed	<8ms
	Scan speed	100HZ/秒
	Touch accuracy	≤2mm
Computer host configuration	Operating system	Support Win 7/8/10; Linux; android
	Service life	Theory unlimited
	Anti-external light test	Full angle resistance to ambient light
	Motherboard	mini ITX architecture
	Main chipset	Intel
	CPU	Support Intel Celeron, Pentium, Core series
	RAM	DDR_4G/8G Optional
	Storage	SSD:32G/64G/128G/256G; HDD:500G
	Graphics card	Nuclear display HD Graphics 3000
	Network card	Integrated 10/100/1000M bps Ethernet
	USB 3.0	3
USB 2.0	3	
EARPHONE	1	
MIC	1	
VGA output	1	
HDMI	1	
WIFI	Scalable 2.4G/5G; 150/300Mbps	
Bluetooth	Scalable	
MIC	1	
Standard motherboard	Model	H3751 V811
	System version	Android 8.0
	Processor	Quad-core MaliG51
	Configuration	Memory 4G DDR3, storage 32G WIFI2.4GHZ +5G (5G projection hotspot)
	Input port	RJ45*1 HDMI*3 TOUCH USB*2 VGA*1 AUDIO IN*1 YPBR*1 AV*1 TV USB*2
	Output port	SPDIF*1 Earphone*1
	Audio	MPEG1/2 layer I/II AC-3 (customization required), AAC-Lc, WMA
	Video	MPEG-2/4, AVS, H.264, H.265, TS, Realmedia
	Sound output power	10W~10W
	Number of speakers	2
	Webcam	Pixel
Output video format		2592*1944, 1920*1080, 1280*720
Number of microphones		4 array microphone/6 array microphone/8 array microphone (optional)
Signal-to-noise ratio		67db
Microphone	Pickup distance	10 meters
	Voltage range	AC 110~240V-50/60HZ
	Power supply	Power consumption: About 660W Standby power consumption: ≤0.5W
Surroundings	Operating temperature	-10° C - 55° C
	Working humidity	10% - 90%RH, No condensation
	Storage temperature	-20C - 60C
	Storage humidity	10% - 90%RH, No condensation
Package	Package Size	2685x280x1730
	Net weight	125kg
	Gross weight	157kg

Ordering Information

Part Number	Display Ports	RAM	Storage	Surface Treatment	Availability
GT-TC-1100CMH-I3-D4-H500	Intel Core i3	4G	500G(HDD)	Clear	Worldwide
GT-TC-1100CMH-I5-D8-S128	Intel Core i5	8G	128G	Clear	Worldwide
GT-TC-1100CMH-I7-D8-S256	Intel Core i7	8G	256G	Clear	Worldwide

To find out more about our extensive range of GreenTouch touch solutions, go to www.greentouch.com.cn, or ifo@greentouch.com.cn

Service call: +86-755-29370883/29371519

Shenzhen GreenTouch Technology Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. GreenTouch (logo) and Shenzhen GreenTouch Technology Co., Ltd. Copyright . All rights reserved.

2016 Shenzhen GreenTouch Technology Co., Ltd. All rights reserved.